







# Screws System

Code	Product name	Photo	Specification		S.S	Titanium
			Diameter	Length		
30234	Locking Screws (Self-tapping)		HA2.0(Torx)	8 to 20mm with 2mm difference	/	Y
			HA2.4(Torx)	8 to 30mm with 2mm difference	/	Y
			HA3.5(Hex)	14 to 50mm with 2mm difference	Y	Y
			HA5.0(Hex)	24 to 50mm with 2mm difference	Y	Y
			HA5.0(Hex)	55 to 90mm with 5mm difference	Y	Y
			HA3.5(Torx)	14 to 50mm with 2mm difference	/	Y
			HA5.0(Torx)	24 to 50mm with 2mm difference	/	Y
			HA5.0(Torx)	55 to 90mm with 5mm difference	/	Y
			HA6.0(Hex)	50 to 100mm with 5mm difference	Y	Y
30235	Cannulated Locking Screws		HA4.0(Hex)	32 to 50 with 2mm difference	/	Y
			HA6.0(Hex)	50 to 100mm with 5mm difference	/	Y
30236	Cortex Screws		HA2.0(Square)	8 to 20mm with 2mm difference	Y	Y
			HA2.0(Torx)	8 to 20mm with 2mm difference	/	Y
			HA2.4(Torx)	8 to 30mm with 2mm difference	/	Y
			HA3.5(Hex)	12 to 60mm with 2mm difference	Y	Y
			HA3.5(Torx)	12 to 60mm with 2mm difference	/	Y
			HA4.5(Hex)	24 to 60mm with 2mm difference	Y	Y
			HA4.5(Torx)	24 to 60mm with 2mm difference	/	Y
30237	Cancellous Screw (Partial-Threaded)		HB4.0(Hex)	20 to 50mm with 5mm difference	Y	Y
			HB6.5(Hex) 16mm	35 to 90mm with 5mm difference	Y	Y
			HB6.5(Hex) 32mm	35 to 90mm with 5mm difference	Y	Y
30238	Cancellous Screw (Full-Threaded)		HB4.0(Hex)	20 to 50mm with 2mm difference	Y	Y
			HB6.5(Hex)	35 to 90mm with 5mm difference	Y	Y
30242	Malleolar Screw		4.5mm(Hex)	30 to 60mm with 2mm difference	Y	Y