

Rayat Grup Tıbbi Cihazlar Ve İmalat San. İth. İhr. DıŞ Tic. Ltd. Şti

+90 212 605 1063 ****** www.rayatgrup.com ******

Power Tools

Code	Product name	Picture	Specification	Unit
SN001	Medical Electric Drill/Saw(Multifunctional, can be sterilized 135℃)	They	(Quick Chuck,Sternum Saw,Craniotomy Mill, Oscillating Saw, Reamer, Cannulated Chuck, Cranial Drill, High-temperature cover), 2 batteries, 1 recharge device, 2 saw bit, Kuitaatanarspeea. 0-12301pm	set
SN002	Medical Electric Drill		No-load Noise:≤40 dB Peak Torque: 5.8N.m Output Power: 95W Temperature rise/5m: ≤20° Component: 1 drill motor, 2 batteries, 1	set
SN003	Medical Electric Saw		Pendulum Frequency: 0-18000osc/m No-load Noise:≤75 dB Output Power: 95W Temperature rise/5m: ≤30° Component: 1 motor, 2 batteries, 1 recharge device, suitcase	set
SN004	Medical Craniotomy Drill		Rotational speed: 0-500rpm No-load Noise:≤65 dB Peak Torque: 9.6N.m Output Power: 50W Temperature rise/5m: ≤25° Drill: 5-13mm Component: 1 motor, 2 batteries, 1 recharge Temperature rise/5m: ≤25°	set
SN005	Medical Electric Sternum Saw		Temperature rise/5m: ≤25° Pendulum Frequency:0-15000osc/m Non-load noise: ≤ 65dB Component: 1 motor, 2 batteries, 1 recharge ROYACO-SIAISSEEL. U-0501pm	set
SN006	Medical Dauluse-Cannulated Electric Drill		No-load Noise:≤40 dB Peak Torque: 12.5N.m Output Power: 100W Temperature rise/5m: ≤20° Component: 1 drill motor, 2 batteries, 1	set
SN007	Medical Electric Acetabular Grinding Drill (Joint Drill,Slow Drill)		Rotational speed: 0-330rpm No-load Noise:≤45 dB Peak Torque: 16.5N.m Output Power: 95W Temperature rise/5m: ≤20° Component: 1 motor, 2 batteries, 1 recharge	set
SN008	Micro Drill for Hand		Component: 1 motor, 2 batteries, 1 recharge No-load Noise:≤40 dB Peak Torque: 2.9N.m Output Power: 50W Temperature rise/5m: ≤20° Component: 1 motor, 2 batteries, 1 recharge	set
SN009	Micro Saw for Hand		load Noise:≤45 dB Radial runout: ≤0.05mm Swing: 4.0° Output Power: 50W Temperature rise/5m: ≤30° Component: 1 motor, 2 batteries, 1 recharge	set

SN010	Micro Cannulated Drill for Hand		No-load Noise:≤45 dB Radial runout: ≤0.05mm Peak Torque: 2.9N.m Output Power: 40W Temperature rise/5m: ≤20° Component: 1 motor, 2 batteries, 1 recharge	set
SN011	Medical electric drill		#wirking workage 9.0v Temperature rise/5m: ≤20° Non-load speed: 0-800rpm Non-load noise: ≤ 63dB Radial runout: ≤0.5mm Charger:Input voltage AC 220V, 50Hz Output power 9.6V, 1.4/1.5A	set
SN012	Craniotomy Mill & Drill		Drill: Rotational speed: 0-820rpm No-load Noise:≤40 dB Mill: Pendulum Frequency: 0-30000osc/m No-load Noise:≤40 dB Output Power: 95W Temperature rise/5m: ≤20° Component: 1 motor, 1 craniotomy mill,1 craniotomy drill,2 batteries, 1 recharge	set
SN013	Medical electric plaster saw		No-load Speed. 0-11000 pm No-load Noise:≤84 dB Diameter of the biggest blade OD: 65mm Power Voltage: 220V / 50Hz Input Power: 115VA	set
SN014	Batterires		Voltage of battery: 14.4V Charging time about 3 hours	PC
SN015	Craniotomy Drill Bit		5-13mm	PC
SN016	Sawing Blade	Mrs. 2 2 2 2 2 2 2 2 2 2	90x13x1.0mm,90x22x1.2mm,90x22x0.8mm,9 0x24x1.2mm,90x24x0.8mm,70x24x1.2mm,70 x24x1.0mm,70x24x0.8mm	PC
SN017	Recharge device	7	Input voltage: 220V/50Hz Output voltage: 14.4V, 900mA	PC
SN018	Drill Bit		Dia:1.1/1.5/2.0/2.5/ 3.0/3.2/3.5/4.0/4.5mm	PC

Aşık Veysel Mah. Reşneli Niyazi Sok. Pazarkent Çarşı AVM 2. Kat No 70 Esenkent – Istanbul / TURKEY

info@rayatgrup.com www.rayatgrup.com